

CAMERA IP FISHEYE 6MP 1.16MM IP67 IK10



Pret: 6793²² RON (fara TVA)

Disponibilitate: Comanda speciala

Descriere

Camer de supraveghere IP Fisheye 6MP Hikvision DS-2CD6365G1-IVS(1.16MM), senzor: 1/1.8 Progressive Scan CMOS, lentila fixa 1.16mm, iluminare: Color: 0.01 Lux @ (F2.25, AGC ON), B/W: 0.005 Lux @ (F2.25, AGC ON), B/W: 0 Lux with IR: 15m, Fisheye View: 2560 × 2560, 2048 × 2048, 1280 × 1280; 180 Panorama View: 2048 × 1536, 1920 × 1440; 180 Dual Channel Panorama View: 2048 × 768, 1920 × 720; Panorama View: 2048 × 1536, 1920 × 1440; 4PTZ View: camera 01/camera 02/camera 03/camera 04: 1024 × 768; Fisheye + 3PTZ View: camera 01: 2048 × 2048, 1024 × 1024, camera 02/camera 03/camera 04: 1024 × 768; 4PTZ Fusion View: 2048 × 1536, 1600 × 1200, compresie: H.265+/H.265/H.264+/ H.264, 4x microfoane incorporate, 1x difuzor incorporat, client: iVMS-4200, iVMS-4500, iVMS-5200, Hik- Connect, Digital WDR, BLC, HLC, 3D DNR, Distortion Correction, Defog, interfete: 1x RJ45 10 M/100 M/1000 M, 1x intrare audio 3.5mm, 1x iesire audio 3.5mm, alarma: 2x intrari, 2x iesiri, 1x RS-485, evenimente: Motion detection, video tampering alarm, alarm input and output, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error), Line crossing detection, intrusion detection, region entrance detection, region exiting detection, scene change detection, audio exception detection, defocus detection, unattended baggage detection, object removal detection, people counting, Queue Management, Heat Map, Intersection Analysis, alimentare: 12 VDC ± 20%, 1 A, PoE: IEEE 802.3af, Class 3, max. 12.5 W, dimensiuni: Ø 140.3 mm × 59.4 mm, greutate: 715g, temperatura de functionare: -40 °C to 60 °C, IP67, IK10