



## **DL MONITOR 24.1" P2426E LED 1920x1200**

**Pret:** 1484<sup>25</sup> RON (fara TVA)

**Disponibilitate:** Comanda speciala

### **Descriere**

Monitor Dell Pro 24.1 P2426E USB-C Hub, 61,13 cm, 1920 x 1200 at 100 Hz, Active matrix-TFT LCD, In-Plane Switching (IPS) Technology, LED Edgelight System, Anti-glare with hard-coating 3H, 16:10, 94, 1500:1 (typical), 178° (vertical) typical, 178° (horizontal) typical, 5 ms (fast mode), 8 ms (normal mode), 300 cd/m<sup>2</sup> (typical), 16.7 million colors, sRGB 99% (CIE 1931) (typical), BT.709 99% (CIE 1931) (typical), Tilt angle -5° to 21°, Swivel: -45° to 45°, Pivot: -90° to 90°, Height adjustable stand 0 mm to 150 mm, Cable management, 100x100, 1 x HDMI (HDCP 1.4) (Supports up to FHD 1920 x 1200, 100 Hz TMDS), 1 x DisplayPort 1.4 (HDCP 1.4) (Supports up to FHD 1920 x 1200, 100 Hz), 1 x DisplayPort 1.4 out with MST (HDCP 1.4) (Supports up to FHD 1920 x 1200, 100 Hz), 1 x USB-C 5Gbps upstream port (DisplayPort 1.4 Alt Mode, Power Delivery up to 96W/100W), 2 x USB 5Gbps Type-A downstream ports, 1 x USB 5Gbps Type-A downstream port (quick access), 1 x USB-C 5Gbps downstream port (quick access, 5V/3A), 1 x RJ45, DDPM compatibility, KVM, MST daisy chain, TUV Rheinland Eye Comfort 3.0 4-star, ComfortView Plus, Flicker Free, Silent Firmware Update (SFU), Security lock slot (cable lock sold separately), Monitor, Stand riser, Stand base, Power cable (varies by country), 1 x USB-C to C 5Gbps 100W cable (1.80 m), QR Card, Safety, Environmental, and Regulatory Information, 531.80 x 511.20 x 181.75 mm (extended), 5.18 kg with stand, 3-Years Advanced Exchange Service and Limited Hardware Warranty