

Placa de baza ASUS PRIME B760M-A WIFI DDR4 LGA1700 Model PRIME B760M-A WIFI D4 CPU Intel® Socket LGA1700 for 13th Gen Intel® Core™ Processors & 12th

Pret: 722<sup>42</sup> RON (fara TVA)

Disponibilitate: Comanda speciala

## **Descriere**

Placa de baza ASUS PRIME B760M-A WIFI DDR4 LGA1700 Model PRIME B760M-A WIFI D4 CPU Intel® Socket LGA1700 for 13th Gen Intel® Core™ Processors & 12th Gen Intel® Core™, Pentium® Gold and Celeron® Processors\* Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0\*\* \*Refer to www.asus.com for CPU support list. \*\* Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types. Chipset Intel® B760 Chipset Memory 4 x DIMM, Max. 128GB, DDR4 5333(OC)/5066(OC)/5000(OC)/4800(OC)/4600

(OC)/4400(OC)/4266(OC)/4000(OC)/3733(OC)/3600(OC)/3466(OC)/3400(OC)/3333 (OC)/3200/3000/2933/2800/2666/2400/2133 Non-ECC, Un-buffered Memory\* Dual Channel Memory Architecture Supports Intel® Extreme Memory Profile (XMP) OptiMem II \* Supported memory types, data rate(Speed), and number of DRAM modules vary depending on the CPU and memory configuration, for more information refer to www.asus.com for memory support list. Graphics 1 x DisplayPort\*\* 2 x HDMI® ports\*\*\* \* Graphics specifications may vary between CPU types. Please refer to www.intel.com for any updates. \*\* Supports max. 4K@60Hz as specified in DisplayPort 1.4. \*\*\* Supports 4K@60Hz as specified in HDMI® 2.1. Expansion Slots Intel® 13th & 12th Gen Processors 1 x PCle 4.0 x16 slot Intel® B760 Chipset 1 x PCle 4.0 x16 slot (supports x4 mode) 1 x PCle 4.0 x16 slot (supports x1 mode) Note: To ensure compatibility of the device installed, please refer to https://www.asus.com/support/ for the list of supported peripherals. Storage Total supports 2 x M.2 slots and 4x SATA 6Gb/s ports\* Intel® 13th & 12th Gen Processors M.2 1 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) Intel® B760 Chipset M.2 2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) 4 x SATA 6Gb/s ports \* Intel® Rapid Storage Technology supports SATA RAID 0/1/5/10. Ethernet 1 x Realtek 2.5Gb Ethernet Wireless & Bluetooth Wi-Fi 6 2x2 Wi-Fi 6 (802.11 a/b/g/n/ac/ax) Supports 2.4/5GHz frequency band Bluetooth v5.2