Placa de baza ASUS ROG STRIX B760-G DDR4 WIFI LGA1700 CPU Intel® Socket LGA1700 for 13th Gen Intel® Core™ Processors & 12th Gen Intel® Core™,

Pret: 1953^{07} RON (fara TVA)

Disponibilitate: Comanda speciala

Descriere

Placa de baza ASUS ROG STRIX B760-G DDR4 WIFI LGA1700 CPU Intel® Socket LGA1700 for 13th Gen Intel® Core™ Processors & 12th Gen Intel® Core™, Pentium® Gold and Celeron® Processors Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0** * Refer to www.asus.com for CPU support list. ** Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types. Chipset Intel® B760 Chipset Memory 4 x DIMM, Max. 128GB, DDR4 5333(OC)/5066(OC)/5000(OC)/4800(OC)/4600(OC)/4400(OC)/4266(OC)/4000 (OC)/3733(OC)/3600(OC)/3466(OC)/3400(OC)/3333 (OC)/3200/3000/2933/2800/2666/2400/2133 MHz Non-ECC, Un-buffered Memory* Dual Channel Memory Architecture Supports Intel® Extreme Memory Profile (XMP) OptiMem II * Supported memory types, data rate(Speed), and number of DRAM module vary depending on the CPU and memory configuration, for more information refer to www.asus.com for memory support list. * Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists). Graphics 1 x DisplayPort** 1 x HDMI®*** * Graphics specifications may vary between CPU types. Please refer to www.intel.com for any updates. ** Support 4K@60Hz as specified in DisplayPort 1.4 *** Support 4K@60Hz as specified in HDMI 2.1. Expansion Slots Intel® 13th & 12th Gen Processors 1 x PCIe 5.0 x16 slot(s) Intel® B760 Chipset 1 x PCIe 4.0 x16 slot (supports x4 mode) 2x PCIe 4.0 x1 slots - To ensure compatibility of the device installed, please refer to https://www.asus.com/support/ for the list of supported peripherals. Storage Total supports 2 x M.2 slots and 4 x SATA 6Gb/s ports* Intel® 13th & 12th Gen Processors M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) Intel® B760 Chipset** M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) 4 x SATA 6Gb/s ports * Intel® Rapid Storage Technology supports SATA RAID 0/1/5/10. Ethernet 1 x Intel® 2.5Gb Ethernet ASUS LANGuard