



## Placa de baza Gigabyte AMD B550M AORUS ELITE

**Pret:** 552<sup>65</sup> RON (fara TVA)

**Disponibilitate:** Comanda speciala

### Descriere

Placa de baza Gigabyte AMD B550M AORUS ELITE, 4 x DDR4 DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory 3rd Gen AMD Ryzen™ Processors: Support for DDR4 4000(O.C.) / 3600(O.C.) / 3333(O.C.) / 3200/2933/2667/2400/2133 MHz memory modules New Generation AMD Ryzen™ with Radeon™ Graphics processors: Support for DDR4 4733(O.C.) / 4600(O.C.) / 4400(O.C.) / 4000(O.C.) / 3600(O.C.) / 3333(O.C.) / 3200/2933/2667/2400/2133 MHz memory modules Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules (Please refer Memory Support List for more information.) 1 x DVI-D port, supporting a maximum resolution of 1920x1200@60 Hz \* The DVI-D port does not support D-Sub connection by adapter. 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz \* Support for HDMI 2.1 version, HDCP 2.3, and HDR. 1 x PCI Express x16 slot (PCIEX16), integrated in the CPU: 3rd Generation AMD Ryzen™ processors support PCIe 4.0 x16 mode 3rd Generation AMD Ryzen™ with Radeon™ Graphics processors support PCIe 3.0 x16 mode \* For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot. 1 x PCI Express x16 slot (PCIEX4), integrated in the Chipset: Supporting PCIe 3.0 x4 mode 1 x PCI Express x1 slot (PCIEX1), integrated in the Chipset: Supporting PCIe 3.0 x1 mode 1 x M.2 connector (M2A\_CPU), integrated in the CPU, supporting Socket 3, M key, type 2242/2260/2280/22110 SSDs: 3rd Generation AMD Ryzen™ processors support SATA and PCIe 4.0 x4/x2 SSDs 3rd Generation AMD Ryzen™ with Radeon™ Graphics processors support SATA and PCIe 3.0 x4/x2 SSDs 1 x M.2 connector (M2B\_SB), integrated in the Chipset, supporting Socket 3, M key, type 2242/2260/2280 SSDs: Supporting SATA and PCIe 3.0 x2 SSDs 4 x SATA 6Gb/s connectors, integrated in the Chipset: Support for RAID 0, RAID 1, and RAID 10 4 x USB 3.2 Gen 1 ports on the back panel Chipset: 2 x USB 3.2 Gen 1 ports available through the internal USB header 6 x USB 2.0/1.1 ports (4 ports on the back panel, 2 ports available through the internal USB header) 1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 2 x system fan headers 2 x addressable LED strip headers 2 x RGB LED strip headers 1 x CPU cooler LED strip/RGB LED strip header 2 x M.2

Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB 3.2 Gen 1 header 1 x USB 2.0/1.1 header 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0\_S module only) 1 x serial port header 1 x Clear CMOS jumper 1 x Q-Flash Plus button 1 x PS/2 keyboard/mouse port 1 x DVI-D port 1 x HDMI port 4 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 1 x RJ-45 port 3 x audio jacks Micro ATX Form Factor